



## 8500 VIBAC® BOPP BOX SEALING TAPE 8500- EASY PRINT

This Easy Printable Ultra Superior Performance packaging tape is specifically designed for automatic carton sealing and other applications that require the most aggressive adhesion in the toughest conditions.

PROPERTIES			
Total thickness micron	72 micron	Total thickness mils	2.830 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Easy Print	Yes	Backing Type	BOPP
Backing thickness micron	50 micron	Adhesive type	Synthetic Rubber
Color	Clear	Tensile strength kg/cm	8,03 kg/cm
Elongation at break	200 %	Adhesion to steel g/cm	622 g/cm
Rolling ball test (RBT) cm	<2 cm	Shear on cardboard	>150 hours
Backing thickness mils	1.970 mils	Tensile strength lb./inch	45.000 lb./inch
Adhesion to steel oz./inch	57 oz./inch	Rolling ball test (RBT) inch	<0.79 inch
Service Temperature F° (Min / Max)	30/140 °F	Service Temperature C° (Min / Max)	(-2)/60 °C
Application Temperature F° (Min / Max)	54/110 °F	Application Temperature C° (Min / Max)	(12)/43 °C
Available width	150.000 mm 144.000 mm 288.000 mm 300.000 mm	Available length	914.000 m 1500.000 m 1828.000 m
Packaging type	jumbo single roll		

8500